Concierge 4-Passenger Gas Specifications

DIMENSIONS

OVERALL LENGTH	128.0 in (3250 mm)
OVERALL WIDTH	47.2 in (1200 mm)
OVERALL HEIGHT (without suntop)	46.9 in (1190 mm)
WHEELBASE	98.1 in (2492 mm)
FRONT WHEEL TREAD	34.3 in (870 mm)
REAR WHEEL TREAD	38.6 in. (980 mm)
MINIMUM GROUND CLEARANCE	4.3 in (110 mm)

ENGINE/DRIVE TRAIN

ENGINE TYPE	Yamaha built, low emission single cylinder 60° incline OHV
DISPLACEMENT	357 cm³
BORE x STROKE	85 x 63 mm
HORSEPOWER	11.4 HP (8.5 Kw / 3500 rpm)
COMPRESSION RATIO	8.1:1
LUBRICATION SYSTEM	Splash style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge
COOLING SYSTEM	Forced air

CARBURETOR	Mikuni BV26-18
IGNITION SYSTEM	Transistor magneto ignition
TRANSAXLE	EnduraDrive™ V-belt automatic forward/reverse transaxle equipped with high-precision helical gears, 11.40:1 drive axle ratio

CHASSIS

FRAME	HybriCore [™] Chassis features a robotically welded automotive ladder-style frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and a electrostatically applied polyester/urethane powder topcoat
BODY (FRONT/REAR)	Custom-formulated thermoplastic olefin, painted with a two-part topcoat of high-luster automotive grade polyurethane
BODY (INTERMEDIATE)	Fiber-reinforced plastic
STEERING	Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tierod ends

FRONT SUSPENSION	Tru-Trak II [™] fully independent automotive-style strut suspension
REAR SUSPENSION	Unit swing arm with coil springs over hydraulic shock absorbers
BRAKES	Maintenance-free internal transaxle disc brake
SEATING	Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a warp and moisture resistant polypropylene bottom, strengthened with plated steel inserts
BUMPERS	Front and rear 5 mph energy-absorbing bumpers
PERFORMANCE	
MAX FORWARD SPEED	15 mph (24 km/h)
MAX REVERSE SPEED	10 mph (16 km/h)
TURNING RADIUS	13.92 ft (4.2 m)

GENERAL

DRY WEIGHT	855 lbs (388 kg)
FUEL TANK CAPACITY	6.3 US gal (24.0 liters)
TIRE SIZE	18.00 x 8.50-8.00 (4-ply rating)
SEATING CAPACITY	4 persons
AVAILABLE PAINT COLORS	Glacier, Emerald, Garnet, Sandstone Metallic, Cobalt Metallic, Anthracite Metallic, Onyx Metallic
AVAILABLE SEAT & SUNTOP COLOR	Stone

WARRANTY

Warranty Standard 2 year limited vehicle warranty

*Specifications subject to change without notice